



# SOLITEX EXTASANA®

## Wall Weather Resistive Barrier

- ✓ 180 days UV resistance & long-term durability
- ✓ Highly vapour permeable (Class 4)
- ✓ Weathertight & airtight weather resistive barrier (WRB)
- ✓ Next generation non-porous monolithic technology

SOLITEX EXTASANA® is a UV stabilised and tear resistant weather resistive barrier (WRB). It contains a non-porous, water resistant TEEE film that is laminated at high temperatures between two layers of spun bonded polypropylene.

This product is designed for use behind most typical wall cladding systems, including cavity brick, fibre-cement, masonry and other common wall systems. It is suitable for use in BAL regions 12.5 to 40 in accordance with AS 3959.

### TECHNICAL DATA

UV stability and outdoor exposure:	180 days	ASTM G154
Duty classification:	Light wall	AS/NZS 4200.1-2017
Vapour classification:	Class 4 (Permeable)	AS/NZS 4200.1-2017
Flammability index:	< 5	AS 1530.2-1993
Thickness:	0.60 mm ± 0.05 mm	EN 1489-2
Temperature resistance:	-40 °C to +120 °C	
Heat shrinkage @ 70°C:	0.0%	ASTM D1204
Water control:	10,000 mm	EN 20811
	Pass (> 100 mm)	AS/NZS 4201.4-1994
	Water barrier	AS/NZS 4200.1-2017

ID CODE	LENGTH	WIDTH	AREA	KG/ROLL	QTY
13547	36.5 m	1.50 m	55 m <sup>2</sup>	8.5	1
13323	36.5 m	2.74 m	100 m <sup>2</sup>	16	1





# Weather Resistive Barrier System

by pro clima

## SOLITEX EXTASANA®

Wall Weather Resistive Barrier

## KAFLEX mono/duo

Cable Sealing Grommet

## TESCON EXTORA®

Weathertight Sealing Tape

## CONTEGA EXO

Joinery Connection Strip - Exterior

## TESCON EXTOSEAL®

Sill Tape

## ROFLEX

Sealing Grommets for Pipes

## ORCON CLASSIC

Multi-Purpose Liquid Adhesive

## TESCON PRIMER RP

Solvent-Free Primer

